

Today's Date:

Quote Due Date:



Quiet Tank Quote Request Form

Customer:Contact:Cell: Phone:Cell: Fax: E-mail:	Location: Required Ship Date:
Car Type:	Project Data:
Single Jack (Direct) Twin Jack Roped Twin Jack (Direct) Telescopic Single Jack (Roped) In Ground	Down Speed Regulated: Y N Muffler: Bladder Chamber Dampener Valve: Maxton EECO Voltage: 3 Phase 200-208 3 Phase 220-240 3 Phase 440-480 3 Phase 575-600
Dry Submersible	Horsepower:
	Speed Up: feet per minute
Available Options:	Speed Down: feet per minute
 Pressure Gauge Oil Return Pump Valve Drain Tank Heater Low Oil Level Switch Oil Cooler Oil Level Sight Gauge Shut-off Valve Under Tank Isolation Low Pressure Switch Oil Viscosity Switch Enclosure with Terminal Block Vent Filler Breather / Protected Overflow Connection Provisions Judick, Sound Absorber 	Capacity: lbs. Relief psi Car Weight: lbs. No Load psi Gross Load: lbs. Full Load psi (Capacity + Car Weight) feet Travel: feet Piston DIA: feet Piston DIA: feet Starts per hour: 80 120 Pipe Size: 2 2.5 3 Tank Outlet: Grooved Threaded Tank Hand: Right Left Coil Voltage: 115 VAC 230 VAC 115 VDC Contact SEES with confidence: 800-526-0026 www.seesinc.com Eav to 954-017-7327 Fav to 954-017-7327 Faveto 954-017-7327
Rouse Sound Absorber	