

Today's Date:	
Quote Due Date:	



Quiet Tank Quote Request Form

Customer: Contact: Phone: Fax: E-mail:	Location: Required Ship Date:
Car Type:	Project Data:
Single Jack (Direct) Twin Jack Roped Twin Jack (Direct) Telescopic Single Jack (Roped)	Down Speed Regulated: Y N Dampener Muffler: Bladder Chamber Dampener Valve: Maxton EECO Voltage: 3 Phase 200-208 3 Phase 220-240
Tank Type:	3 Phase 440-480 1 Phase 240
Submersible Rush - \$500 Strut - \$300 Controller Mounting Dwg Appvl Required Options:	Horsepower: feet per minute Speed Down: feet per minute
Pressure Gauge Oil Viscosity Switch	Capacity: lbs. Relief psi Car Weight: lbs. No Load psi
Low Oil Level Switch Tank Heater	Gross Load: lbs. Full Load psi (Capacity + Car Weight) Telescopic
Oil Level Sight Gauge Oil Cooler Under Tank Isolation Scavenger Pump	Travel: feet DIA 1: Piston DIA: inches DIA 2:
Low Pressure Switch Drain Port	Hertz: 50 60 DIA 3:
Conduit Box with Terminal Block	Starts per hour: 80 120
Ball Valve	Pipe Size: 2 2.5 3
Acoust blok. Sound Absorber	Tank Outlet: Grooved Threaded Tank Hand: Left Right
Lid Only Entire Tank	Coil Voltage: 115 VAC 230 VAC 115 VDC
Notes:	

Contact SEES with confidence:

800-526-0026

www.SEESinc.com Fax to 954-917-7337

 ${\bf Email\ for\ quote:\ orders@SEES inc.com}$